PB90-166349

Proposed Best Demonstrated Available Technology (BDAT) Background Document for D011, P099 and P104. Volume 23

(U.S.) Environmental Protection Agency, Washington, DC

Nov 89

U.S. Department of Commerce
National Technical Information Service
NTIS

50272-101

REPORT DOCUMENTATION PAGE	1. REPORT NO. EPA/530-SW-90-011W	2.	3. PB90-166349
4. Title and Subtitle PROPOSED BEST DEMONSTRATED AVAILABLE TECHNOLOGY (BDAT) BACKGROUND DOCUMENT FOR D011, P099, AND P104 (ADDENDUM)			5. Report Date NOVEMBER 1989 6.
7. Author(s) ROSENGRANT/CHATMON			8. Performing Organization Rept. No
9. Performing Organization Name and Address U.S. EPA Office of Solid Waste 401 M. Street SW Washington, DC 20460			10. Project/Task/Work Unit No. 11. Contract(C) or Grant(G) No. (C) (G)
12. Sponsoring Organization Name and Address			13. Type of Report & Period Covered BACKGROUND DOCU. - 11/89 14.

15. Supplementary Notes

16. Abstract (Limit: 200 words)

This background document presents the Agency's technical support and rationale for developing regulatory standards for these wastes. Sections 2 through 6 present waste-specific infomration for the D011 wastes. Section 7 discusses associated silver-containing P-code wastes and details the development of treatment standards for these wastes.

17. Document Analysis a. Descriptors

b. Identifiers/Open-Ended Terms

c. COSATI Field/Group

18. Availability Statement	19. Security Class (This Report)	21. No. of Pages
RELEASE UNLIMITED	UNCLASSIFIED	0
	20. Security Class (This Page) UNCLASSIFIED	22. Price 0

(See ANSI-Z39.18)

REPRODUCED BY
U.S. DEPARTMENT OF COMMERCE
NATIONAL TECHNICAL INFORMATION SERVICE
SPRINGFIELD, VA. 22161

OPTIONAL FORM 272 (4-77)
(Formerly NTIS-35)

EPA/530-SW-90-011W

PROPOSED
BEST DEMONSTRATED AVAILABLE TECHNOLOGY (BDAT) BACKGROUND DOCUMENT FOR D011, P099 AND P104

Larry Rosengrant, Chief
Treatment Technology Section

Monica Chatmon-McEaddy
Project Manager

U.S. Environmental Protection Agency
401 M Street, S.W.
Washington, D.C. 20460

November 1989

Table of Contents

		Page No.
1.	INTRODUCTION	1-1
2.	INDUSTRIES AFFECTED AND WASTE CHARACTERIZATION	2-1
	2.1 Industries Affected and Process Descriptions	2-1
	2.1.1 Production of Silver Chemicals	2-1
	2.1.2 Uses of Silver Chemicals	2-2
	2.2 Waste Characterization	2-4
	2.3 Determination of Waste Treatability Group	2-5
3.	APPLICABLE AND DEMONSTRATED TREATMENT TECHNOLOGIES	3-1
	3.1 Applicable Treatment Technologies	3-1
	3.1.1 Treatment Technologies for Nonwastewaters	3-1
	3.1.2 Treatment Technologies for Wastewaters	3-3
	3.2 Demonstrated Treatment Technologies	3-3
4.	PERFORMANCE DATA BASE	4-1
5.	IDENTIFICATION OF BEST DEMONSTRATED AVAILABLE TECHNOLOGY (BDAT)	5-1
6.	DEVELOPMENT OF BDAT TREATMENT STANDARDS	6-1
7.	P WASTE CODES	7-1
	7.1 Industries Affected	7-1
	7.2 Applicable and Demonstrated Treatment Technologies	7-1
	7.3 Determination of Best Demonstrated Available Technology	7-2
	7.4 Selection of Regulated Constituents	7-2
	7.5 Calculation of Proposed Treatment Standards	7-3
8.	REFERENCES	8-1

LIST OF TABLES

		Page No.
Table 1-1	Proposed BDAT Treatment Standards for D011, P099, and P104 Nonwastewaters	1-4
Table 1-2	Proposed BDAT Treatment Standards for D011, P099, and P104 Wastewaters	1-4
Table 2-1	U.S. Industrial Distribution of Silver and Its Compounds	2-3
Table 4-1	Treatment Performance Data for Stabilization of F006 Waste	4-3
Table 6-1	Calculation of Proposed Treatment Standards for D011 Nonwastewaters	6-3
Table 6-2	Proposed BDAT Treatment Standards for D011 Nonwastewaters	6-4
Table 6-3	Proposed BDAT Treatment Standards for D011 Wastewaters	6-4
Table 7-1	Proposed BDAT Treatment Standards for P099 and P104 Wastewaters	7-4
Table 7-2	Proposed BDAT Treatment Standards for P099 and P104 Nonwastewaters	7-5

1. INTRODUCTION

Pursuant to section 3004(m) of the Hazardous and Solid Waste Amendments (HSWA), enacted on November 8, 1984, the Environmental Protection Agency (EPA) is establishing treatment standards based on best demonstrated available technology (BDAT) for the silver-containing wastes identified in 40 CFR 261.24 as the waste code D011 and for commercial chemical product wastes identified in 40 CFR 261.33 as P099 - potassium silver cyanide and P104 - silver cyanide. Treatment standards for cyanide for P099 and P104 wastes were promulgated with the Second Third land disposal restriction final rule (54 FR 26614, June 23, 1989). Compliance with treatment standards is a prerequisite for placement of these wastes in facilities designated as land disposal treatment units according to 40 CFR Part 268. The effective date of the final promulgated treatment standards for silver in D011, P099, and P104 wastes will be May 8, 1990.

This background document presents the Agency's technical support and rationale for developing regulatory standards for these wastes. Sections 2 through 6 present waste-specific information for the D011 wastes. Section 2 identifies the number and location of facilities affected by the land disposal restrictions for D011 wastes, discusses processes generating these wastes, and presents all available waste characterization data. Section 3 discusses the technologies used to treat the waste (or similar wastes), and Section 4 presents available performance data, including data on which treatment standards are based. Section 5 explains EPA's determination of BDAT. Proposed treatment standards are determined in Section 6. Section 7 discusses associated silver-containing P-code wastes and details the development of treatment standards for these wastes.

The BDAT program and promulgated methodology are more thoroughly described in two additional documents: Methodology for Developing BDAT Treatment Standards (USEPA 1989a) and the Generic Quality Assurance Project Plan for Land Disposal Restrictions Program ("BDAT") (USEPA 1988a). The petition process to be followed in requesting a variance from the BDAT treatment standards is discussed in the methodology document.

It is EPA's understanding that relatively few facilities presently generate D011 wastes. From a partial analysis of responses to EPA's 1986 National Survey of Hazardous Waste Generators, the Agency has identified 35 facilities that generate D011 wastes. These wastes are primarily the wastewater treatment sludges from the production and use of silver compounds. For the purpose of BDAT these are usually nonwastewaters. A wastewater is defined by the Agency as containing less than 1 percent (weight basis) total suspended solids* and less than 1 percent (weight basis) total organic carbon (TOC). Wastes not meeting this definition must comply with the treatment standards for nonwastewaters.

The proposed BDAT for nonwastewater forms of D011, P099, and P104 is recovery or stabilization and the proposed treatment standard is 0.072 mg/l, based on treatment data from stabilization of F006 wastes. The Agency realizes that because of its economic value, silver is generally recovered from wastes where it is contained at relatively high concentrations. However, the Agency also realizes that wastes with low silver content or with the silver present in the form of difficult-to-process compounds may not be suitable for most recovery technologies.

---

* The term "total suspended solids" (TSS) clarifies EPA's previously used terminology of "total solids" and "filterable solids." Specifically, the quantity of total suspended solids is measured by Method 209c (Total Suspended Solids Dried at 103 to 105°C) in Standard Methods for the Examination of Water and Wastewater, 15th Edition (APHA, AWWA, and WPCF 1985).

The proposed BDAT for D011, P099, and P104 wastewaters is chemical precipitation and the proposed treatment standard is 0.29 mg/l, determined by analysis of a 24-hour composite sample. As an alternative to chemical precipitation, facilities may also remove and recover silver from wastewaters by chemical reduction to form silver metal. The proposed BDAT treatment standards for D011, P099, and P104 nonwastewaters and wastewaters are listed in Table 1-1 and Table 1-2, respectively.

Table 1-1 Proposed BDAT Treatment Standards for
D011, P099, and P104 Nonwastewaters

Regulated Constituent	Maximum for any single grab sample TCLP (mg/l)
Silver	0.072

Table 1-2 Proposed BDAT Treatment Standards for
D011, P099, and P104 Wasteswaters

Regulated Constituent	Maximum for any 24-hour composite sample Total composition (mg/l)
Silver	0.29

2. INDUSTRIES AFFECTED AND WASTE CHARACTERIZATION

The Agency has determined that D011 wastes represent a single treatability group for nonwastewaters and one for wastewaters based on their similar physical and chemical characteristics. As described later in this report, EPA has examined the sources of the wastes, specific similarities in waste composition, applicable and demonstrated treatment technologies, and attainable treatment performance in order to support a simplified regulatory approach for silver-containing wastes.

2.1 Industries Affected and Process Descriptions

2.1.1 Production of Silver Chemicals

Silver is used in industry in two forms--as the metal and as various silver compounds. Presently, eight silver compounds are produced in commercial quantities. These eight silver compounds are discussed below.

Silver nitrate represents the largest volume of silver-containing chemical manufactured. Its production involves digestion of silver in nitric acid to form a silver nitrate solution that is partially evaporated and fed to crystallizers to recover silver nitrate crystals. The mother liquor is recycled. Wastes from this process are in the form of wastewaters. Treatment of these wastewaters generates residues containing silver that are either reclaimed when the silver content is high enough or land disposed when the silver content is low (i.e., below about 1 percent).

Other silver salts are produced from the silver nitrate. Silver chloride, bromide, and iodide, for example, are produced by reaction of silver nitrate in solution with sodium chloride, bromide, or iodide. The

insoluble product precipitates from solution, is recovered by filtration, and then is washed and dried. These processes give rise to waterborne wastes, the treatment of which results in silver-bearing residues. Silver oxide, carbonate, and sulfide are made by similar processes involving reaction in aqueous solution of silver nitrate with sodium hydroxide, sodium carbonate, or sodium sulfide, respectively. In all cases, the products precipitate from solution and are then collected by filtration and dried.

Silver cyanide is produced by reaction of sodium cyanide and silver nitrate in solution under carefully controlled conditions. Again, the insoluble product precipitates from solution, is collected by filtration, and then is washed, dried, and packaged. Treatment of the wastewaters generated by this process yields silver-bearing residues.

2.1.2 Uses of Silver Chemicals

Table 2-1 lists the major uses of silver and its alloys. The largest use is in the photographic industry, where silver chloride, bromide, and iodide are used in the manufacture of photographic films. Both the manufacture and subsequent processing (developing) of the films generate a variety of silver-containing nonwastewaters and wastewaters. Wastewater treatments generate silver-bearing sludges, which are mostly reclaimed for silver value.

Brazing solders frequently contain silver chloride as a fluxing agent, and the manufacture and use of these solders generate wastes containing silver chloride. The production of silver oxide-zinc batteries gives rise to wastewaters and nonwastewaters containing silver. The same is true for the production and reclamation of silver oxide catalysts.

Table 2-1 U.S. Industrial Distribution of Silver and Its Compounds

Industry	Silver compounds used	Percent
Photographic film manufacturing	Nitrate, halides	41.2
Electrical contacts	Metal	21.6
Brazing alloys and solders	Chloride	7.4
Sterling silverware	Metal	6.8
Batteries	Oxide	5.3
Jewelry	Metal	4.1
Electroplating	Cyanide	3.5
Coins and medallions	Metals	3.5
Catalysts	Oxide	3.3
Dental and medical supplies	Metal	1.6
Mirrors	Nitrate	0.5
Bearings	Metal	0.2
Other	Metal	1.0
		100.0

Electroplating operations consume considerable quantities of silver cyanide and complex silver cyanide salts such as potassium silver cyanide. The listed wastes generated by these operations (F006, F007, F008, and F009) are discussed in EPA's BDAT Background Document for F006 (USEPA 1988b) and BDAT Background Document for Cyanide Wastes (USEPA 1989c).

In the production of mirrors, two separate solutions, one of an ammonia-complexed silver nitrate and the other containing an organic compound such as formaldehyde, are reacted on the glass surface to be coated. A coating of silver forms on the glass surface. The mirror is then rinsed and a silicone coating may be applied to protect the silvered surface. This process generates waterborne wastes containing silver. Subsequent treatment of the wastewaters generates silver-bearing residues.

2.2 Waste Characterization

The Agency has data from EPA's National Survey of Hazardous Waste Generators (USEPA 1986) on the approximate composition of the types of D011 wastes currently generated. The nonwastewater forms of D011 contain from 0.1 up to 100,000 parts per million of silver. Other metals are generally present at comparable concentrations. Most nonwastewaters contain very low levels of organics. The wastewater forms of D011 contain from 0.1 to 10,000 parts per million of silver. Frequently, other metals are also present. In a few cases, organics may be present at concentrations up to 1 percent. Cyanides are usually not present because most silver-cyanide electroplating wastes are reclaimed rather than disposed.

Most of the facilities reporting D011 wastes in the Generator Survey were plants producing photographic chemicals, electronics equipment, or aerospace-related products. The nature of the individual processes generating the waste streams is quite varied and includes most of the operations identified as significant consumers of silver salts.

2.3 Determination of Waste Treatability Group

Characteristic wastes (i.e., D-code wastes) may have the same waste code but be produced in different processes in an industry or in different industries. This can result in the wastes having different waste characteristics, such that the wastes may not be treatable to similar concentrations using the same technology. In these instances, the Agency may subdivide waste codes into several treatability groups. This is done when the chemical forms of the wastes are different and clearly require different treatments or combinations of treatments. For example, inorganic and organometallic compounds containing the same metal(s) frequently require different types of treatment.

Based on a careful review of the generation of D011 wastes and available waste characterization data, the Agency has determined that all D011 nonwastewaters form a single treatability group. The Agency has also determined the same to be true for D011 wastewaters. The concentration of silver in the various wastes is dependent on the waste type, the particular production process employed, and the specifics of the treatment process used. However, all of these wastes contain silver in a similarly treatable form and are thus expected to be treatable to similar levels using the same technologies.

3. APPLICABLE AND DEMONSTRATED TREATMENT TECHNOLOGIES

Section 2 established a single treatability group for nonwastewaters and another for wastewaters for the management of D011 wastes. This section identifies the treatment technologies that are applicable to treatment of these wastes and determines which, if any, of the applicable technologies can be considered demonstrated for the purpose of establishing BDAT.

To be applicable, a technology must be theoretically usable to treat the waste in question or to treat a waste that is similar in terms of the parameters that affect treatment selection. (For detailed descriptions of the technologies applicable for these wastes, or for wastes judged to be similar, see EPA's Treatment Technology Background Document (USEPA 1989b.) To be demonstrated, the technology must be employed in full-scale operation for the treatment of the waste in question or a similar waste. Technologies available only at pilot- and bench-scale operations are not considered in identifying demonstrated technologies.

3.1 Applicable Treatment Technologies

3.1.1 Treatment Technologies for Nonwastewaters

Four types of technologies are applicable to nonwastewater forms of D011: silver recovery technologies and chemical reduction, chemical precipitation, and stabilization technologies. Chemical reduction and chemical precipitation are primarily wastewater treatment technologies; therefore, they are discussed in Section 3.1.2. Nonwastewaters may be slurried in water, if necessary, and treated by these wastewater treatment technologies.

(1) Silver recovery technologies. Three types of silver recovery technologies are in use today: electrolytic recovery, cementation

processes, and high-temperature recovery processes (Lockhart 1981). Electrolytic recovery involves digestion of the waste to solubilize the silver present followed by electrolysis of the silver-bearing solution generated. This is the process most frequently used to recover silver from photographic film. The silver recovered by electrolysis is generally sent to precious metals refineries for purification prior to reuse.

Cementation is an oxidation/reduction process for recovery of metallic silver. Cementation processes involve initial digestion of the waste to solubilize the silver. The silver-containing solution is filtered to remove insoluble residues, and a finely divided non-noble metal, such as zinc dust, is added. Zinc dissolves in the solution, replacing the silver, which precipitates as silver metal. The silver metal is recovered and sent to a precious metal refinery.

Recovery of silver in residues generated by chemical precipitation or reduction processes also involves an initial digestion of the waste to solubilize the silver, followed by wastewater treatment as described in the next section. Residues from the wastewater treatment processes (nonwastewaters) are collected by filtration and sent to a precious metals reclaimer, where the impure silver recovered is purified by high-temperature processes to yield a 99.9 percent purity product. The reclamation process involves roasting of the silver sulfide filter cake to thermally convert it to the metal and subsequent refining of the metal.

(2) Stabilization. Residues generated by chemical treatment processes such as chemical reduction and sulfide precipitation may be treated for silver recovery as described in the Section 3.1.1(1) or stabilized with lime, cement, or fly ash formulations prior to land disposal. Stabilization technologies are discussed in the Treatment Technology Background Document (USEPA 1989b).

3.1.2 Treatment Technologies for Wastewaters

The silver recovery processes and chemical treatment processes described above are applicable to wastewaters as well as nonwastewaters. The chemical treatment processes will either reduce silver salts to the metal for recovery or precipitate silver as insoluble silver salts such as silver sulfide or silver chloride.

(1) Chemical reduction. In chemical reduction technologies, the waste is treated with a solution containing a reducing agent such as ferrous salt or sodium bisulfite. The reducing agent reacts with the soluble silver compounds present to generate elemental silver, which precipitates from solution. Chemical reduction technologies are discussed in greater detail in the Treatment Technology Background Document (USEPA 1989b).

(2) Chemical precipitation. Sulfide precipitation converts soluble silver salts to insoluble silver sulfide. Chloride compounds may also be used to remove silver from wastewaters as insoluble silver chloride. Chemical precipitation technologies are discussed in greater detail in the Treatment Technology Background Document (USEPA 1989b).

3.2 Demonstrated Treatment Technologies

Silver recovery technologies (e.g., electrolysis, cementation, and high-temperature recovery) have been in widespread use in the photographic chemicals and photographic processing industries for over a decade. A 1977 study, for example, showed extensive use of these technologies at photographic processing facilities (Haderer and DeFilippi 1977). These technologies were installed primarily for economic reasons (i.e., to maximize silver recovery and minimize silver losses).

Chemical reduction, chemical precipitation, and stabilization are demonstrated technologies that have been in full-scale use for many years in industry. In fact, effluent limitations guidelines for several segments of the inorganic chemicals industry are based on the use of chemical reduction and chemical precipitation technologies (USEPA 1982).

4. PERFORMANCE DATA BASE

This section presents the data available to EPA on the performance of demonstrated technologies in treating the listed wastes. These data are used elsewhere in this document for determining which technologies represent BDAT (Section 5) and for developing treatment standards (Section 6). Eligible data, in addition to full-scale demonstration data, may include data developed at research facilities or obtained through other applications at less than full-scale operation, as long as the technology is demonstrated in full-scale operation for a similar waste or wastes, as defined in Section 3.

Performance data, to the extent that they are available to EPA, include the untreated and treated waste concentrations for a given constituent, values of operating parameters that were measured at the time the waste was being treated, values of relevant design parameters for the treatment technology, and data on waste characteristics that affect the performance of the treatment technology.

Where data are not available on the treatment of the specific wastes of concern, the Agency may elect to transfer data on the treatment of a similar waste or wastes using a demonstrated technology. To transfer data from another waste category, EPA must find that the wastes covered by this background document are no more difficult to treat (based on the waste characteristics that affect performance of the demonstrated treatment technology) than the treated wastes from which performance data are being transferred.

The Agency has data on the effectiveness of recovery technologies in those industries using silver salts, such as the photographic processing industries. Most of these data have been accumulated from earlier Agency studies aimed at developing effluent limitations guidelines for the

photographic industry (USEPA 1976). The data basically show that with the use of one or more of the silver recovery systems, photographic processing plants could meet the 1977 effluent limitations guidelines for silver (as a time-weighted average) of 0.45 mg/l in their wastewaters. All recovery processes are aqueous processes, and residual concentrations of silver in the process solutions were readily reduced to below 0.45 mg/l.

The Agency also has extensive data on the use of chemical reduction and precipitation processes to remove silver from aqueous solution (USEPA 1982). These data, obtained for the purpose of setting effluent limitations guidelines for the silver nitrate subcategory of the inorganic chemicals industry, show that concentrations of below 0.45 mg/l can be obtained for silver ions in solution by use of these processes.

The Agency also has extensive data on the use of chemical precipitation and stabilization on the waste F006, which sometimes contains silver. These data are included in Table 4-1.

Additional wastewater treatment data, primarily from EPA's Office of Water, have been analyzed for the development of concentration-based treatment standards for D011 and other wastewaters. Further information on these data, including the sources of the data and the treatment technologies used, can be found in the preamble to the proposed rule and in the Best Demonstrated Available Technology (BDAT) Background Document for Wastewaters Containing BDAT List Constituents (USEPA 1989d).

Table 4-1 Treatment Performance Data for Stabilization of F006 Waste

Constituent	Concentration: Untreated waste Total (mg/kg)	Untreated waste TCLP (mg/l)	Treated waste - TCLP (mg/l) Binder-to-waste ratio[a] 0.2	0.5	1.0	1.5
Sample Set #1 (Source-unknown)						
Silver	2.3	0.01	0.03	NR	NR	NR
Oil and grease	1,520	-	-	-	-	-
TOC	14,600	-	-	-	-	-
Sample Set #2 (Source-auto parts manufacturing)						
Silver	6.62	0.14	0.03	0.05	NR	NR
Oil and grease	60	-	-	-	-	-
TOC	1,500	-	-	-	-	-
Sample Set #3 (Source-aircraft over-hauling facility)						
Silver	39.0	0.02	0.20	0.05	NR	NR
Oil and grease	37,000	-	-	-	-	-
TOC	137,000	-	-	-	-	-
Sample Set #4 (Source-aerospace manufacturing-mixture of F006 & F007)						
Silver	6.26	1.64	NR	NR	0.09	0.15
Oil and grease	3,870	-	-	-	-	-
TOC	8,280	-	-	-	-	-
Sample Set #5 (Source-zinc plating)						
Silver	9.05	0.16	0.03	0.04	NR	NR
Oil and grease	1,150	-	-	-	-	-
TOC	21,200	-	-	-	-	-
Sample Set #6 (Source-unknown)						
Silver	5.28	0.08	0.04	0.06	NR	NR
Oil and grease	20,300	-	-	-	-	-
TOC	28,600	-	-	-	-	-

Table 4-1 (continued)

Constituent	Concentration: Untreated waste Total (mg/kg)	Untreated waste TCLP (mg/l)	Treated waste - TCLP (mg/l) Binder-to-waste ratio[a] 0.2	0.5	1.0	1.5
Sample Set #7 (Source-small engine manufacturing)						
Silver	4.08	0.12	0.03	0.05	NR	NR
Oil and grease	2,770	-	-	-	-	-
TOC	6,550	-	-	-	-	-
Sample Set #8 (Source-circuit board manufacturing[b])						
Silver	12.5	0.05	0.03	0.05	NR	NR
Oil and grease	130	-	-	-	-	-
TOC	550	-	-	-	-	-
Sample Set #9 (Source-unknown)						
Silver	8.11	0.31	0.03	0.05	NR	NR
Oil and grease	30	-	-	-	-	-
TOC	10,700	-	-	-	-	-
Sample Set #10 (Source-unknown)						
Silver	19.1	<0.01	<0.01	<0.01	NR	NR
Oil and grease	1,430	-	-	-	-	-
TOC	5,960	-	-	-	-	-

- = Not applicable.

NR = Results of tests at this binder-to-waste ratio were not reported.

[a]Binder-to-waste ratio = $\frac{\text{weight of binder material}}{\text{weight of waste}}$

[b]Oil and grease and total organic carbon (TOC) have been identified by EPA as waste characteristics that affect the performance of stabilization.

[c]Circuit board manufacturing waste is not in its entirety defined as F006; however, an integral part of the manufacturing operation is electroplating. Treatment residuals generated from treatment of these electroplating wastes are F006.

Source: CWM 1987.

5. IDENTIFICATION OF BEST DEMONSTRATED AVAILABLE TECHNOLOGY (BDAT)

This section presents the Agency's rationale for determining best demonstrated available technology (BDAT) for nonwastewater and wastewater forms of D011.

To determine BDAT, the Agency examines all available performance data on technologies that are identified as demonstrated to determine (using statistical techniques) whether one or more of the technologies performs significantly better than the others. The technology that performs best on a particular waste or waste treatability group is then evaluated to determine whether it is "available." To be available, the technology must (1) be commercially available to any generator and (2) provide "substantial" treatment of the waste, as determined through evaluation of accuracy-adjusted data. In determining whether treatment is substantial, EPA may consider data on the performance of a waste similar to the waste in question, provided that the similar waste is at least as difficult to treat. If the best technology is found to be not available, then the next best technology is evaluated, and so on.

The most desirable waste management technology is one that results in no residual streams or a residual stream with no hazardous properties. In this instance, silver recovery eliminates the D011 waste streams in many cases. This is especially true for wastewaters, where most if not all of the silver can be recovered from these waste streams as metal. For nonwastewater forms of D011, recovery technologies will also reduce the concentrations of silver present in wastes to be land disposed.

The Agency realizes, however, that not all nonwastewater and wastewater forms of D011 may be readily amenable to recovery processes. Silver may be present in refractory solid matrices from which it cannot

be easily extracted, or it may be present in solution in the form of complex ions that cannot easily be treated by recovery processes. For nonwastewater forms of D011 wastes from which silver cannot be recovered, the best technology has been determined to be stabilization, based on data on stabilization of wastewater treatment sludges (F006) with significant concentrations of leachable silver (up to 1.64 mg/l in the untreated waste TCLP leachate). Stabilization has been shown to reduce the leachability of silver in these wastes. Accordingly, the Agency has determined that either recovery or stabilization represent BDAT for nonwastewater forms of D011.

For wastewaters where silver recovery is not viable, chemical treatment is the best technological treatment option. Chemical treatment (either chemical reduction or chemical precipitation) will remove soluble silver salts either as the metal or as insoluble silver compounds. EPA has data that show that chemical precipitation and filtration are used for treatment of most D011 wastewaters from which silver is not recovered, and results in the generation of wastewater residuals for which silver concentration is substantially reduced from the concentration in the untreated waste. Accordingly, the Agency has determined that chemical precipitation followed by filtration represents BDAT for D011 wastewaters.

EPA has determined that the best demonstrated technologies specified above for the D011 treatability groups (i.e., chemical precipitation followed by sedimentation and filtration for wastewaters and recovery or stabilization for nonwastewaters) are also commercially available and provide substantial treatment. Hence, these technologies represent BDAT for D011 wastewaters and nonwastewaters, respectively.

6. DEVELOPMENT OF BDAT TREATMENT STANDARDS

In Section 5, the Agency chose the best demonstrated available technology (BDAT) for both nonwastewaters and wastewaters based on the treatment data available to the Agency. In this section, proposed BDAT treatment standards will be developed based on the performance of these technologies. Silver is selected as the only regulated constituent because it is the only constituent for which this waste is listed. If D011 wastes are mixed with other listed or characteristic hazardous wastes and thus contained other constituents, other treatment standards would also apply.

The Agency bases treatment standards for regulated constituents on the performance of well-designed and well-operated BDAT treatment systems. These standards must account for analytical limitations in available performance data and must be adjusted for variabilities related to treatment, sampling, and analytical techniques and procedures.

BDAT standards are determined for each constituent by multiplying the arithmetic mean of accuracy-adjusted constituent concentrations detected in treated waste by a "variability factor" specific to each constituent for each treatment technology defined as BDAT. Accuracy adjustment of performance data takes into account the analytical recoveries associated with sample analysis to correct for analytical interferences caused by the waste matrix. Variability factors account for normal variations in the performance of a particular technology over time. They are designed to reflect the 99th percentile level of performance that the technology achieves in commercial operation. (For more information on the principles of calculating variability factors, see EPA's publication Methodology for Developing BDAT Treatment Standards (USEPA 1989a).) Details on the calculation of variability factors for silver-containing nonwastewaters and wastewaters are presented in this section.

As discussed in Section 5 of this document, the Agency realizes that all wastewaters and nonwastewaters containing silver may not be amenable to recovery, but has not identified silver concentrations or waste characteristics that would define whether or not a D011 waste is recoverable.

For D011 nonwastewaters, the Agency is therefore proposing a treatment standard of 0.072 mg/l as measured in the TCLP leachate. This treatment standard is based on the transfer of treatment data from stabilization treatment of F006 wastes. The calculation of this treatment standard is shown in Table 6-1.

For D011 wastewaters, the Agency is proposing a treatment standard of 0.29 mg/l based on the data from analysis of various treated wastewaters under the Agency's Effluent Guideline Program. Calculation of the proposed treatment standard for D011 wastewaters is discussed in the BDAT background document for wastewaters containing BDAT list constituents (USEPA 1989b).

Tables 6-2 and 6-3 show the proposed treatment standards for D011 nonwastewasters and wastewaters, respectively.

Table 6-1 Calculation of Proposed Treatment Standards for D011 Nonwastewaters

Regulated constituent	Accuracy-adjusted treated waste leachate concentration (mg/l) (1)	Mean treated waste leachate concentration (mg/l) (2)	Variability factor (VF)[a] (3)	Treatment standard (TCLP) (mg/l) (4) = (2) (3)
Silver	0.03	0.04	1.8	0.072
	0.08			
	0.03			
	0.03			
	0.03			
	0.03			

[a] See Methodology Document (USEPA 1989a) for details of the method of calculation of variability factor.

Table 6-2 Proposed BDAT Treatment Standards for D011 Nonwastewaters

Regulated Constituent	Maximum for any single grab sample TCLP (mg/l)
Silver	0.072

Table 6-3 Proposed BDAT Treatment Standards for D011 Wasteswaters

Regulated Constituent	Maximum for any 24-hour composite sample Total composition (mg/l)
Silver	0.29

7. P WASTE CODES

This section addresses regulation of P-code wastes that are listed for silver. These wastes, P099 - potassium silver cyanide and P104 - silver cyanide, are identified in 40 CFR 261.33 as "discarded commercial chemical products, off-specification species, container residues, and spill residues thereof". Treatment standards for cyanide in P099 and P104 wastes were promulgated with the Final Rule for Second Third Wastes (54 FR 26614, June 23, 1989). Therefore, this section will only address the development of a treatment standard for silver in P099 and P104 wastes. Detailed information on the development of cyanide treatment standards for P099 and P104 wastes is included in the BDAT background document for cyanide wastes (USEPA 1989c).

7.1 Industries Affected

Silver cyanide is prepared by the reaction of silver nitrate and sodium cyanide under carefully controlled conditions. Potassium silver cyanide is prepared by reacting silver nitrate with potassium cyanide. Silver cyanide and potassium silver cyanide are used in the metal finishing industry in electroplating operations as a source of soluble silver. Additional information on the industries affected by the land disposal restrictions for silver wastes is presented in Section 2.1.

7.2 Applicable and Demonstrated Treatment Technologies

The treatment technologies described in Section 3 as being applicable and demonstrated for D011 silver wastes are also considered to be applicable and demonstrated for P099 and P104 wastes. EPA has no other data suggesting that other treatment technologies are applicable or demonstrated for silver in P099 and P104 wastes.

7.3 Determination of Best Demonstrated Available Technology

EPA believes that P099 and P104 wastes, as commonly generated, are similar to D011 wastes. Silver cyanide is a relatively insoluble compound (approximately 0.2 ppm silver). Therefore, these wastes will be generated primarily as nonwastewaters. However, these wastes may have to be dissolved in order to treat them for cyanide by aqueous chemical oxidation treatment methods.

Based on performance data on the treatment of silver-containing wastes as presented in Section 4, the Agency has identified chemical precipitation followed by sedimentation and filtration as the "best" treatment for P099 and P104 wastewaters. For P099 and P104 nonwastewaters, the Agency has identified recovery or stabilization as the "best" treatment.

EPA has also determined that the best demonstrated technologies specified above for P099 and P104 wastewaters and nonwastewaters are commercially available and provide substantial treatment. Hence, these technologies represent BDAT for P099 and P104 wastewaters and nonwastewaters.

7.4 Selection of Regulated Constituents

EPA is proposing a treatment standard for silver in P099 and P104 wastes. Treatment standards for cyanide in P099 and P104 wastes were promulgated in the Final Rule for Second Third Wastes (54 FR 26614 June 23, 1989). Silver and cyanide are the only Appendix VIII constituents for which P099 and P104 wastes are listed, and they are the only BDAT list constituent that the Agency expects to find in the wastes on a regular basis (unless these wastes are mixed with other listed hazardous wastes, in which case other treatment standards would also apply).

7.5 Calculation of Proposed Treatment Standards

For P099 and P104 wastewaters, the Agency is proposing a treatment standard for silver based on the performance of chemical precipitation followed by sedimentation and filtration. The calculation of this treatment standard is presented in the Best Demonstrated Available Technology (BDAT) Background Document for Wastewaters Containing BDAT List Constituents (USEPA 1989d). The proposed treatment standard for P099 and P104 wastewaters is summarized in Table 7-1.

For P099 and P104 nonwastewaters, the Agency is proposing that recovery or stabilization represent BDAT for these wastes. The proposed treatment standard, based on the performance of stabilization of F006 wastes, is 0.072 mg/l as measured by the TCLP leachate. The calculation of this standard is shown in Table 6-1. The proposed treatment standard for P099 and P104 nonwastewaters is summarized in Table 7-2.

Table 7-1 Proposed BDAT Treatment Standards
for P099 amd P104 Wastewaters

Regulated Constituent	Maximum for any 24-hour composite sample Total composition (mg/l)
Silver	0.29

Table 7-2 Proposed BDAT Treatment Standards for P099 amd P104 Nonwastewaters

Regulated Constituent	Maximum for any single grab sample TCLP (mg/l)
Silver	0.072

8. REFERENCES

APHA, AWWA, and WPCF. 1985. Americal Public Health Association, American Water Works Association, and Water Pollution Control Federation. Standard methods for the examination of water and wastewater. 16th ed. Washington, D.C.: American Public Health Association.

Haderer, P.A., and DeFilippi, J.A. 1977. Reducing photoprocessing wastes through reuse and recycling. Industrial Photography. June 1977. pp 22-45.

Lockhart, H.B. 1981. Silver compounds. In Kirk Othmer encyclopedia of chemical technology, Vol. 21, pp. 16-32. New York: John Wiley-Interscience.

Stanford Research Institute. 1989. Directory of chemical producers, United States of America. Stanford Research Institute, Menlo Park, California.

USEPA. 1976. U.S. Environmental Protection Agency, Office of Water. Development document for effluent limitations guidelines and new source performance standards for the photographic processing subcategory of the photographic point source category. Washington, D.C.: U.S. Environmental Protection Agency.

USEPA. 1982. U.S. Environmental Protection Agency, Office of Water. Development document for effluent limitations guidelines (BATEA), new source performance standards and pretreatment standards for the inorganic chemicals manufacturing point source category. Washington, D.C.: U.S. Environmental Protection Agency.

USEPA. 1986. U.S. Environmental Protection Agency, Office of Solid Waste. National survey of hazardous waste generators. Washington, D.C.: U.S. Environmental Protection Agency.

USEPA. 1988a. U.S. Environmental Protection Agency, Office of Solid Waste. Generic quality assurance project plan for the land-disposal restrictions program ("BDAT"). Washington, D.C.: U.S. Environmental Protection Agency.

USEPA. 1988b. U.S. Environmental Protection Agency, Office of Solid Waste. Best demonstrated available technology (BDAT) background document for F006. Washington, D.C.: U.S. Environmental Protection Agency, Office of Solid Waste.

USEPA. 1989a. U.S. Environmental Protection Agency, Office of Solid Waste. Methodology for developing BDAT treatment standards. Washington, D.C.: U.S. Environmental Protection Agency.

USEPA. 1989b. U.S. Environmental Protection Agency, Office of Solid Waste. Treatment technology background document. Washington, D.C.: U.S. Environmental Protection Agency.

USEPA. 1989c. U.S. Environmental Protection Agency, Office of Solid Waste. Best demonstrated available technology (BDAT) background document for cyanide wastes. Washington, D.C.: U.S. Environmental Protection Agency.

USEPA. 1989d. U.S. Environmental Protection Agency, Office of Solid Waste. Best demonstrated available technology (BDAT) background document for wastewaters containing BDAT list constituents. Washington, D.C.: U.S. Environmental Protection Agency.